

## ETERNABOND

### RoofSeal PLUS

#### Description

Designed specifically for granulated roofs and surfaces that require a deeper seal. **RoofSeal PLUS** features a UV stable backing that is available in White and Black. It also features **EternaBond's** advanced **MicroSealant™ Technology**. Therefore, with the exception of cleaning the repair surface, **RoofSeal PLUS** is literally a one-step permanent repair system. **RoofSeal PLUS** creates a waterproof, moisture and air tight barrier. **RoofSeal PLUS** remains flexible to temperatures as low as -70° F.

**RoofSeal PLUS** features **EternaBond's** self-sealing advanced **MicroSealant™ Technology**, a sealant so advanced it permanently bonds to a wide range of surfaces including difficult roof materials such as : EPDM, TPO, most PVC, CSPE/Hypalon, CPE, SBS, APP modified, asphalt BURs, coal tar BURs, all metal roofs, tiles, shingle, aluminum, galvanized steel, gypsum board, wood, polyethylene, propylene, polystyrene, fiberglass, brick, concrete, masonry, OSB, etc.

#### Basic Use

**EternaBond RoofSeal PLUS** is used whenever a thicker layer of **EternaBond's** self-sealing advanced **MicroSealant™** is needed to reach deeper into a surface. Designed to seal granulated roof joints (seams) and tears, it is also extremely effective on flashings, copings, skylights, gutters, etc. **RoofSeal PLUS** seals to itself so it can be cut and folded around an object, as if wrapping a present.

#### Technical Data

Standard roll size	2", 4", 6" X 25'
Standard case quantity	50 sq. ft. per case
Available widths	Up to 48"
Colors	Black and White
Total thickness	65 mils (+/- 2 mils)
Adhesion	20 lbs +/-in width
Low temp flexibility	1/2" radius at -30° F
Application temp	>150° F to -25° F with optional primer
Temperature range	-70° F - >200° F
Pliability	No cracks in membrane
Water vapor test (ASTME 96B)	.005 grms/100" sq. / 24 hrs / 100° F
Permeance	.001 perms maximum
Elongation	<700 % +/- 100
Tensile break PSI	4500 PSI +/- 500 PSI
Shelf life	Up to 5 years
Values are typical performance properties and characteristics based on laboratory testing. This is intended as a guide for comparison purposes and does not constitute a specification or specification range.	

#### Composition

**EternaBond RoofSeal PLUS** utilizes **EternaBond's** **MicroSealant™ Technology**, a 100% solids formulation of synthetic resins, thermoplastics and non-curing rubbers with a built in primer, bonded to a tough UV stable backing. Designed not to harden under even the most rigorous conditions. **MicroSealant™** is protected (while in a roll) by a tough, easily removed siliconized polymer release liner, which prevents contamination prior to its use.

**CAUTION:** All statements and technical information in this document are based on tests or data that ADCO believes is reliable. However, ADCO does not warrant or guarantee the accuracy or completeness of this information. The user has sole knowledge and control of factors that can affect the performance of ADCO's products in the user's intended application. It is the user's responsibility to conduct tests to determine the compatibility of ADCO's product with the design, structure, and materials of the user's end product and the suitability of ADCO's product for the user's method of application and intended use. The user assumes all risk and liability arising out of such use.

## Surface Preparation

Surface must be clean and dry; free of loose rust and scale, dust, talc and dirt. Oil, grease and other contaminants should be removed with a suitable solvent/cleaner. Use of **EternaPrime** reduces clean up. For older plastic roofs, score surface with sand cloth and wipe away dust.

## Application

Install **EternaBond RoofSeal PLUS** over the repair area, removing the plastic release liner gradually to prevent contamination of the adhesive prior to application. Rub or roll with pressure with and or steel roller to activate bonding process. This material may be applied to clean dry surfaces from 150° F to -20° F. Treat surface with **EternaPrime** for installations from 40° F to -20° F.

Available from Major Electronix | [sales@majorelectronix.com](mailto:sales@majorelectronix.com) | 800-966-2345 | [www.productsforautomation.com](http://www.productsforautomation.com)

EternaBond RoofSeal PLUS R2 02/15/12

---

**WARRANTY:** ADCO warrants its products to conform to ADCO's specifications at the time of sale when tested according to ADCO standards. If a product is proven to be defective when tested according to ADCO standards, ADCO will, at its option, refund the purchase price or replace or repair the defective product. THIS LIMITED WARRANTY IS THE BUYERS SOLE AND EXCLUSIVE REMEDY AGAINST ADCO AND IS IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event shall ADCO be liable for any special, incidental, consequential, or punitive damages arising out of any claims whether based on negligence, contract, warranty, strict liability or otherwise.