

▶▶▶ 6 Port Industrial Ethernet Ring Switch

The SL/SLX-6RS is a 6 port industrial Ethernet switch featuring Sixnet's Real-Time-Ring™ which provides very fast, fault-tolerant network redundancy and prioritized message delivery needed in critical real-time systems. These Rings self-configure and just run, without the complex configuration steps required by alternative solutions. This advanced technology delivers reliability and performance, saves you money, and makes your job easier.

PRODUCT HIGHLIGHTS

- 6 ports including up to 2 fiber optic
- Super-fast, fault-tolerant ring redundancy
- Pre-configured for true plug & play simplicity
- Truly industrial hardened design
- Slim case for DIN rail or direct panel mounting

REAL-TIME FAULT-TOLERANT RINGS

- Recovery time of 30 mS plus 5 mS per hop!
- Ideal for deterministic systems and PLCs
- Real-time Modbus over Ethernet monitoring

REAL-TIME TRAFFIC PRIORITIZATION (QoS)

- Assure delivery of real-time data
- Improve network utilization
- User settable priority assignments

MANAGED SWITCH FEATURES – at a lower cost

- User configurable port settings
- Port mirroring for traffic diagnostics
- Message filtering to prevent broadcast storms

TROUBLE FREE OPERATION

- Ultra-reliable 1,000,000 + hours MTBF
- -40 to +85 °C operating range (SLX model)
- UL/CSA (CUL), CE and Hazloc (Zone 2) rated
- Dual (redundant) power inputs
- Industrial surge and spike protection
- Self-test/alarm output contact



SL/SLX-6RS-1/4/5 Industrial Ethernet Switch Specifications

ETHERNET PERFORMANCE

- 6 fast Ethernet ports with up to 2 fiber
- Managed, store & forward, wire-speed
- All IEEE 802.3 Ethernet protocols supported
- RJ45 ports (shielded) 10/100BaseTX
- RJ45 port speed auto-negotiation
- RJ45 MDI/MDIX auto-crossover
- RJ45 TD and RD auto-polarity
- Fiber optional on port 5 and 6
- Fiber optic port speed: 100 Mbps
- Fiber typical specs (see separate datasheet for details)
 - Multimode, 4 km, 1310 nm, 50-62.5/125 μ m
 - Singlemode, 20 km, 1310 nm, 9-10/125 μ m
 - Long haul, up to 120 km, 1550 nm, 9-10/125 μ m
- Typical latency (varies on load & settings)
 - @ 10 Mbps: 16 us + frame time
 - @ 100 Mbps: 5 us + frame time
- Full or half duplex operation configurable per port
- MAC addresses supported 2048
- Memory bandwidth 3.2 Gbps
- Ethernet isolation 1500 VRMS 1 minute

ETHERNET COMPLIANCE

- IEEE 802.3u (Fast Ethernet 100Mbps for newer devices)
- IEEE 802.3 (10Mbps Ethernet supports legacy devices)
- IEEE 802.1p (Priority Queuing – QoS, CoS, ToS/DS)
- IEEE 802.3x (Full-Duplex with Flow Control)

REAL-TIME-RING™

- Link loss recovery: 30 mS plus 5 mS per hop
- Switches in a ring: <50 for best performance
- Multiple rings supported (configurable)

“OK” ALARM OUTPUT

- Indicates power & operational status
- Voltage same as switch input voltage
- Maximum current output 0.5 Amp

POWER INPUT

- Redundant input terminals
- Reverse polarity protection
- Input power (typ. with all ports active)
 - 4 W (-1 model w/ no fiber)
 - 6 W (-4/5 model w/ 2 fiber)
- Power input voltage 10-30 VDC
- Transient protection 15,000 watts peak
- Spike protection 5,000 watts (10x for 10 uS)

ENVIRONMENTAL

- Operating temperature:
 - SLX: -40 to +85 °C (cold startup at -40 °C)
 - SL: -40 to +60 °C
- Storage temperature -40 to +85 °C
- Humidity (non-condensing) 5 to 95% RH (optional conformal coating is available)
- Vibration and shock – IEC60068-2-6, -27
- Maximum Operating Altitude: 30,000 ft.

STANDARDS COMPLIANCE

- Electrical safety – UL508 / CSA C22.2/142; EN61010-1, CE
- EMC – FCC part 15, ICES-003; EN61000-6-2/4, CE
- Hazardous locations – ANSI/ISA 12.12.01 / CSA C22.2/213 (Class I, Div. 2); EN60079-15 (Zone 2, Category 3), CE (ATEX)
- Maritime – designed for marine and offshore per ABS
- RoHS and WEEE compliant

PHYSICAL


- DIN rail or direct panel mounting
- Case – Aluminum (SLX) or Lexan (SL)
- Ingress protection
 - SL models: IP30
 - SLX models: IP40
- Weight – SLX: 0.23 kg (8 oz.); SL: 0.17 kg (6 oz.)
- Dimensions – see mechanical diagram

ORDERING GUIDE

SLX-6RS-1-D1	6 RJ45 ports, metal case, wide temp.
SLX-6RS-4SC-D1	4 RJ45 ports, 2 multimode SC, 4 km
SLX-6RS-4ST-D1	4 RJ45 ports, 2 multimode ST, 4 km
SLX-6RS-5SC-D1	4 RJ45 ports, 2 singlemode SC, 20 km
SLX-6RS-5ST-D1	4 RJ45 ports, 2 singlemode ST, 20 km
SLX-6RS-5SCL-D1	4 RJ45 ports, 2 singlemode SC, 40+ km
SLX-6RS-5STL-D1	4 RJ45 ports, 2 singlemode ST, 40+ km
SL-	w/ Lexan case and limited temperature
Setup Wizard	Free - Windows configuration tool
ET-PS-024-02	Power supply – AC to 24VDC, 2A
SP-ETH-2	Dual port Ethernet surge & lightning protector for 10/100 ports

NOTE: The suffix 1 means it is pre-configured for 1 ring on ports 5 & 6. Contact SIXNET for other pre-configuration options.

MECHANICAL DRAWING



All specifications are subject to change. Consult factory for latest info.



www.redlion.net

Connect. Monitor. Control.

Americas
sales@redlion.net

Asia-Pacific
asia@redlion.net

Europe
Middle East
Africa
europe@redlion.net

+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our automation, Ethernet and cellular M2M technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. Red Lion is part of Spectris plc, the productivity-enhancing instrumentation and controls company. For more information, please visit www.redlion.net.

ADLD0329 091916 © 2016 Red Lion Controls, Inc. All rights reserved. Red Lion, the Red Lion logo, N-Tron and Sixnet are registered trademarks of Red Lion Controls, Inc. All other company and product names are trademarks of their respective owners.