

INSTALLATION GUIDE

MODEL #: ECS-150W1050

LED Commercial Fixture
Canopy Light | Square Class



PLEASE REVIEW THE INSTRUCTIONS AND WARNINGS LISTED BELOW PRIOR TO PROPER INSTALLATION

WARNINGS

- · Do not use the electric generator to test the LED lamp.
- Please abide by related country, regional and local law and regulations when installing this fixture.
- Please turn off the power before installation or maintenance.
- · Proper grounding is required to ensure safety.

WARNING/ AVERTISSEMENT


MIN 75°C SUPPLY CONDUCTOR

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

IMPORTANT


- To avoid possibility of electrical shock or fire, the installation personnel must have professional electric knowledge.
- · Please wear gloves to avoid injury before installation.
- If smoke or fire is found in wires or led fixture during or after installation, please turn off the power immediately and notify relevant personnel.
- Please check if there is any damage during shipping. If so, please contact manufacturer immediately.
- Please read the installation instruction carefully to check whether all the accessories are complete. After confirmation, then install the fixture according to the installations.

WIRING DIAGRAM





INSTALLATION (1)

- Fix one side of the accessory safety rope on the back of the fixture.
- 2 Use electric drill to set fixed holes through the ceiling.



Fix another side of safety rope on the ceiling, then connect the wire of fixture to main power source according to local electrical connection code, make sure the wire joints are well protected, after that, fix the fixture on the ceiling with accessory screws.







INSTALLATION GUIDE


MODEL #: ECS-150W1050

LED Commercial FixtureCanopy Light|Square Class




PLEASE REVIEW THE INSTRUCTIONS AND WARNINGS LISTED BELOW PRIOR TO PROPER INSTALLATION


INSTALLATION (2)




Connect the wiring to the local power supply in the 3/4"NPT Stem.



INSTALLATION (3-1)




Fix the mounting bracket on the back of fixture with supplied screws.




- 2 Unscrew the nut from customer supplied 3/4"NPT stem, make the stem hole on mounting bracket through 3/4"NPT stem, then screw the nut back to 3/4"NPT, and fix it.
- Make wiring connections per "Electrical Connections" section and make sure the wires are well protected.

INSTALLATION (3-2)


Drill the alignment holes on the top ceiling, to match the holes on mounting bracket.



Insert the supplied rubbers into the alignment holes, then fix the mounting plate on the ceiling with supplied screws.



- Mount the fixture on the mounting plate with supplied screws.
- Make wiring connections per "Electrical Connections" section and make sure the wires are well protected.



RECOMMENDED DIMMER LIST

LUTON: NTSTV-DV / LEVITON: DS710-10Z / LEVITON: IP710 / Legrand: RH4FBL3PW