# NTPS-24-1.3 Power Supply

N-Tron Networking Series



# **DIN Rail Mount Power Supply**

The NTPS-24-1.3 is a DIN rail mount power supply designed to be used with N-Tron's Industrial Ethernet products.

#### **INPUT SPECIFICATIONS:**

AC Voltage 100-240VAC Frequency 47 to 63Hz

Input Current <0.6A @ AC 100Vin

<0.35A @ AC 196Vin 36A max. @240VAC

DC Voltage 85-375VDC

#### **OUTPUT SPECIFICATIONS:**

Inrush Current

Output Voltage 24-28VDC Maximum Load 1.3A Ripple & Noise <50mVpp Voltage Accuracy  $\pm 2\%$ 

### **ENVIRONMENTAL CHARACTERISTICS:**

Full Nominal Load -10°C - 60°C -25°C - 85°C Storage Temperature Cooling Natural Convection

#### **MECHANICAL CHARACTERISTICS:**

45w x 75h x 91d (mm) Dimensions

1.8" x 3.0" x 3.6"

Weight 230g (0.5 Pounds)

## **REGULATORY APPROVALS:**

#### **Hazardous Locations:**

UL 1604 Listed, Class I Division 2 Hazardous Location Groups A, B, C, D



### Safety:

CE ,EN 60950, EN 60204-1, EN 50178, IEC60950,


UL 60950, UL 508


CAN/CSA-C22.2 No. 60950 (CUR) CAN/CSA-C22.2 No. 14 (CUL) EN 61000-6-3 and -4 (Emissions)


(EN 55011, EN 55022, Class B)

EN 61000-6-2 and EN 61000-6-1 (Immunity)

VDE 0160/W2 (Transient protect)









#### www.redlion.net

Connect. Monitor. Control.

**Americas** sales@redlion.net

Asia-Pacific asia@redlion.net

Europe Middle East **Africa** 

europe@redlion.net

+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our award-winning technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. For more information, please visit www.redlion.net. Red Lion is a Spectris company.